

# TRANSACTION DESK SPECIFICATION

## Types of units:

- Transaction desk solutions (Modular units that connect in the field)
  - Workstations – tables and transaction counters in straight and curved versions
  - Cabinets – fixed at worksurface height and mobile to slide under worksurface
  - Book returns

## Standard features on modular transaction desk units:

- 1" thick 45lb. multi-density particleboard substrate with a balanced construction of color-matched, thermally fused laminate (TFL) on both sides of all ends. .75" thick back panels, shelves, doors, drawer fronts; and toe kicks.
- Worksurfaces with 1" thick 45lb. multi-density particleboard substrate feature a balanced construction with high pressure laminate (HPL) on top and .5mm cabinet liner backer on bottom of worksurface.
- Permanently attached 3mm color-matched or coordinating PVC edge band with ergonomic 1/8" radiused edge bonded with hot-melt adhesive and trimmed flush on all visible edges of bottom panels, shelves, and drawer fronts and bottom edges of end panels to create pick-proof moisture-resistant edges.
- Permanently attached .018" color-matched or coordinating PVC edge band bonded with hot-melt adhesive and trimmed flush on sides of top and back panels, and on the back of end panels.
- Structural 1.25" high metal support rail under worksurface to control deflection.
- Units feature butt-joint construction. End panels, back panels, bottom panels, toe kicks, worksurfaces, and top supports fastened with 16-gauge steel brackets fastened with #8 x 5/8" panhead screws. Transaction counter attached with VHB adhesive tape.
- 16- and 20-gauge cold-rolled steel drawer construction on box and file drawers mounted to 16" non-binding full-extension drawer slides on both box and file drawers. Drawers finished with electrostatically applied powder coating.
- Hinges are European style with 120-degree swing and soft close feature.
- Individual drawer and door cylinder-type locking mechanisms on closed storage units keyed alike within the cabinet.
- Door and drawer pulls are ADA compliant arch-shaped pulls that are 128mm on center, 148mm in length with 30mm projection. Optional Metro pull is 128mm on-center, 138mm in length with 25mm projection.
- 3" diameter cable passthrough grommets on select units. Hole to be added in the field.
- .75" thick particleboard shelving secured with metal screws so shelving cannot be accidentally dislodged. Shelf placement holes on 32mm increments allow for shelf repositioning in field.
- Individual modular transaction desk unit configuration is arranged and joined in the field. Units can be repositioned over their lifetime as desired.
- Units joined in field with tight-joint fasteners at top and bottom of unit.
- Transition and end panels conceal hardware and provide a finished appearance.
- Shipped assembled independently with casters attached if applicable.

### Surface materials palette:

- Thermally Fused Laminate (TFL) available in woodgrains, solids, or patterns. 31 standard colors with coordinating edgeband colors.
- High Pressure Laminate (HPL) available in wood grain, patterned, or solid color palette. 31 standard options with coordinating edgeband colors. Wilsonart laminates also available as a graded-in custom material.
- Custom TFL and HPL (worksurfaces only) through specials request process with coordinating 3mm vinyl edgeband.
- Buying relationships established with Wilsonart, Formica, Nevamar, Pionite/Panolam, and other suppliers.

### Overall:

- Cloth blanket wrapped and carton packaging options are available. If cartoned, skids are made from recycled materials.

### Warranty highlights:

- Fleetwood brand products carry a limited lifetime warranty, where products are warranted to be free of defects in materials and workmanship for the life of the product.
- Normal wear-and-tear is not covered under the warranty. Unauthorized alterations, improper maintenance, or abuse nulls warranty.
- Fleetwood will repair or replace free-of-charge any component that fails under normal use or provide refund or credit.
- Laminates, casters, levelers, and flip-and-nest mechanisms have a 12-year warranty.
- Some products have limited life coverage of 3 or 5 years. See full warranty statement for details.
- Consumables, natural variations in product, and select non-standard products not covered under limited lifetime warranty.
- See full warranty statement for details.